

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/042457 A2

- (51) International Patent Classification⁷: **G02F**
- (21) International Application Number:
PCT/US2003/035381
- (22) International Filing Date:
5 November 2003 (05.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/423,903 5 November 2002 (05.11.2002) US
60/490,111 25 July 2003 (25.07.2003) US
- (71) Applicant (for all designated States except US): **DONNELLY CORPORATION** [US/US]; 414 East Fortieth Street, Holland, MI 49423 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MCCABE, Ian,**


A. [IE/US]; 16092 Ransom Street, Holland, MI 49424 (US). **VARAPRASAD, Desaraju** [US/US]; 1281 Innisbrook Court, Holland, MI 49423 (US). **HABIBI, Hamid** [IR/US]; 190 Standish, Holland, MI 49423 (US). **LYNAM, Niall, R.** [US/US]; 248 Foxdown, Holland, MI 49424 (US).

(74) Agents: **VAN DYKE, GARDNER, LINN & BURKHART, LLP** et al.; 2851 Charlevoix Drive SE P.O. Box 888695, Grand Rapids, MI 49588-8695 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: **ELECTRO-OPTIC REFLECTIVE ELEMENT ASSEMBLY**



(57) Abstract: An electro-optic reflective element assembly (510) includes a pair of substrates (512, 514) and an electro-optic medium (516) sandwiched therebetween. Each of the pair of substrates includes at least one conductive or semi-conductive layer (518, 520) disposed thereon. The electrical connections may electrically connect to a respective layer and may be electrically isolated from the other layer, such as via non-conductive regions (514e) of the substrates and/or deletion lines along one of the conductive layers. The pair of substrates may be positioned relative to one another such that overhang portions (512h, 512i) of the front substrate (512) extend beyond the corresponding edges of the rear substrate (514). The overlapping relationship may provide clearance for electrical connection to the conductive layers of the front and rear substrates such that the electrical connections are substantially not viewable through the front substrate.



(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.